

SECTION 16A

TOILET ACCESSORIES

16A-01 SCOPE: The work covered under this section consists in furnishing all plant, labor, equipment, and materials not furnished by the Government, and in performing all operations in connection with the furnishing and installation of all toilet room accessories, complete, in strict accordance with this section of the specifications and applicable drawings, and subject to the terms and conditions of the contract.

16A-02 MATERIALS: Materials and products required under this section of the specifications shall be the standard products of the manufacturer. Where manufacturers' specific item numbers are used descriptively to establish the construction, quality and design of the item desired, like items similar in design and equal in construction and quality may be substituted at the option of the Contractor with the approval of the Contracting Officer.

a. Accessories for Bath Rooms shall be similar to Set K-6 as manufactured by the Fairfacts Company Incorporated, Trenton, New Jersey, or approved equal and shall be furnished and installed in each Bath Room of the 2-Bed Room Duplexes and 4-Man BOQs in accordance with the following tables:

<u>Quan.</u>	<u>Description</u>	<u>Cat. No.</u>
1	Soap Holder for Tub	F152
1	Soap Holder for Lavatories	F115
1	Tumbler Holder	F160
1	Toilet Paper Holder	F2
2	Towel Bars	F300

b. Curtain Rods shall be furnished and installed in each tub recess in the manner indicated on the drawings. Rods shall be of 1-inch diameter metal tubing having a wall thickness not less than 0.045 inches with cast flanges at wall with set screws. Rods, flanges and screws shall be chromium plated over nickel plating and conform to Figure 66 of Federal Specification WW-P-541a.

c. Medicine Cabinets: One recessed medicine cabinet with mirror door of the size indicated on the drawings shall be provided in each Bath Room at location indicated on the drawings. The cabinet body and backing for the door shall be made of steel not less than 0.0368 inch in thickness. The mirror shall be No. 1 quality plate-glass mirror not less than 3/16 inch thick, double-silvered and protected with electro-deposited copper and protective paint. The mirror shall be framed with a channel of chromium-plated brass or corrosion-resisting steel. The cabinet shall be provided with a razor-blade slot and with three adjustable bulb-edged glass shelves. The door shall be hung on piano hinge and shall be fitted with bullet catch and bar stop. Two rubber bumpers shall be provided on the door or on the cabinet. Hinge, catch, stop and shelf supports shall be made of chromium-plated brass or corrosion-resisting steel. The cabinet body and backing for door shall have enamel finish.

16A-01

d. Toilet Paper Holder (Maid's Toilet): One toilet paper holder conforming to the requirements of Federal Specification WW-P-541, type 435, shall be installed in each Maid's Toilet in the 2-Bed Room Duplexes.

16A-03 INSTALLATION: Toilet accessories of the types specified herein shall be installed where indicated on the drawings and as directed by the Contracting Officer in conjunction with the fixtures they are selected for as hereinbefore specified. Toilet accessories or devices which are of recessed pattern shall be securely attached to supporting work. Devices or supports requiring to be built in shall be erected at the appropriate time to coordinate with work of other trades.